

HOT-WATER CLEANERS

1000 series



Supplied with:

- 10 meter **2-layer** high pressure hose
- Pistol grip handle
- **Stainless** steel double lance with high and low pressure nozzle
- 10 meter power cable with plug
- 80 Kw burner with quick and efficient heating
- Flame surveillance and hour counter

Tank gauge as optional extra

Tank gauge is available for the mobile hot-water cleaner only.



MODEL	WORKING PRESSURE/ BAR	WATER USAGE L/MIN.	MAX TEMPERATURE	PUMP PISTONS	MOTOR-CAPACITY KW/HK	VOLTAGE	LENGTH MM.	WIDTH MM.	HEIGHT MM.	NOZZLE	WEIGHT KG.
1015	150	15	110°	3	4.0/5.5	3x230/400	1000	680	760	1505	135
1016	160	14	110°	3	4.0/5.5	3x230/400	1000	680	760	15045	135
1018	170	18	110°	3	5.5/7.5	3x230/400	1000	680	760	1506	150
1018s	200	18	110°	3	6.5/9.0	3x230/400	1000	680	760	15055	150
1019	150	21	110°	3	5.5/7.5	3x230/400	1000	680	760	15075	150
1019s	170	21	110°	3	6.5/9.0	3x230/400	1000	680	760	1507	150
1020	200	15	110°	3	5.5/7.5	3x230/400	1000	680	760	15045	150
1020s	240	15	110°	3	6.5/9.0	3x230/400	1000	680	760	1504	150
1021	200	21	110°	3	7.5/10	3x230/400	1150	750	820	15065	175
1021s	300	21	110°	3	11	3x230/400	1150	750	820	15055	190
1025	170	25	110°	3	7.5/10	3x230/400	1150	750	820	1508	175
1025ECO	150	25	110°	3	6.5/9.0	3x230/400	1150	750	820	1509	175
1030	150	30	110°	3	7.5/10	3x230/400	1150	750	820	1510	175



Can be supplied with frequency control:

- Working tasks that demands variable pressure settings
- Stable cleaning of all kinds
- Multi-user cleaning

MODEL	WORKING PRESSURE/ BAR	WATER USAGE L/MIN.	MAX TEMPERATURE	PUMP PISTONS	MOTOR-CAPACITY KW/HK	VOLTAGE	LENGTH MM.	WIDTH MM.	HEIGHT MM.	NOZZLE	WEIGHT KG.
1015-ST	150	15	110°	3	4.0/5.5	3x230/400	1000	580	750	1505	105
1016-ST	160	14	110°	3	4.0/5.5	3x230/400	1000	580	750	15045	105
1018-ST	170	18	110°	3	5.5/7.5	3x230/400	1000	580	750	1506	135
1018s-ST	200	18	110°	3	6.5/9.0	3x230/400	1000	580	750	15055	145
1019-ST	150	21	110°	3	5.5/7.5	3x230/400	1000	580	750	15075	135
1019s-ST	170	21	110°	3	6.5/9.0	3x230/400	1000	580	750	1507	145
1020-ST	200	15	110°	3	5.5/7.5	3x230/400	1000	580	750	15045	135
1020s-ST	240	15	110°	3	6.5/9.0	3x230/400	1000	580	750	1504	145
1021-ST	200	21	110°	3	7.5/10	3x230/400	1000	580	750	1506	175
1021s-ST	300	21	110°	3	11	3x230/400	1000	580	750	1506	190
1025-ST	170	25	110°	3	7.5/10	3x230/400	1000	580	750	1508	175
1025ECO-ST	150	25	110°	3	6.5/9.0	3x230/400	1150	750	820	1509	175
1030-ST	150	30	110°	3	7.5/10	3x230/400	1000	580	750	1510	190